
www.DataSheet4U.com

N-CHANNEL ENHANCEMENT-MODE POWER MOSFET

- Low gate-charge
- Simple drive requirement
- Fast switching




BV_{DSS}	30V
$R_{DS(ON)}$	12mΩ
I_D	45A

Description

The SSM60T03H is in a TO-252 package, which is widely used for commercial and industrial surface mount applications, and is well suited for low voltage applications such as DC/DC converters. The through-hole version, the SSM60T03J in TO-251, is available for low-footprint vertical mounting. These devices are manufactured with an advanced process, providing improved on-resistance and switching performance. The devices have a maximum junction temperature rating of 175°C for improved thermal margin and reliability.



TO-252 (H)



TO-251 (J)

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	±20	V
I_D @ T_C=25°C	Continuous Drain Current, V_{GS} @ 10V	45	A
I_D @ T_C=100°C	Continuous Drain Current, V_{GS} @ 10V	32	A
I_{DM}	Pulsed Drain Current[1]	120	A
P_D @ T_C=25°C	Total Power Dissipation	44	W
	Linear Derating Factor	0.352	W/°C
E_{AS}	Single Pulse Avalanche Energy[3]	29	mJ
T_{STG}	Storage Temperature Range	-55 to 175	°C
T_J	Operating Junction Temperature Range	-55 to 175	°C

Thermal Data

Symbol	Parameter	Max.	Units
Rthj-c	Thermal Resistance Junction-case	3.4	°C/W
Rthj-a	Thermal Resistance Junction-ambient	110	°C/W

www.DataSheet4U.com

www.DataSheet4U.com

www.DataSheet4U.com

Electrical Characteristics @ T_j=25°C (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250uA	30	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C, I_D=1mA	-	0.026	-	V/°C
$R_{DS(ON)}$	Static Drain-Source On-Resistance[2]	V_{GS}=10V, I_D=20A	-	-	12	mΩ
		V_{GS}=4.5V, I_D=15A	-	-	25	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250uA	1	-	3	V
g_{fs}	Forward Transconductance[2]	V_{DS}=10V, I_D=10A	-	25	-	S
I_{DSS}	Drain-Source Leakage Current (T_j=25°C)	V_{DS}=30V, V_{GS}=0V	-	-	1	uA
	Drain-Source Leakage Current (T_j=175°C)	V_{DS}=24V ,V_{GS}=0V	-	-	250	uA
I_{GSS}	Gate-Source Leakage	V_{GS}= ± 20V	-	-	±100	nA
Q_g	Total Gate Charge[2]	I_D=20A	-	11.6	-	nC
Q_{gs}	Gate-Source Charge	V_{DS}=24V	-	3.9	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	V_{GS}=4.5V	-	7	-	nC
$t_{d(on)}$	Turn-on Delay Time[2]	V_{DS}=15V	-	8.8	-	ns
t_r	Rise Time	I_D=20A	-	57.5	-	ns
$t_{d(off)}$	Turn-off Delay Time	R_G=3.3Ω , V_{GS}=10V	-	18.5	-	ns
t_f	Fall Time	R_D=0.75Ω	-	6.4	-	ns
C_{iss}	Input Capacitance	V_{GS}=0V	-	1135	-	pF
C_{oss}	Output Capacitance	V_{DS}=25V	-	200	-	pF
C_{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	135	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage[2]	I_S=45A, V_{GS}=0V	-	-	1.3	V
trr	Reverse Recovery Time	I_S=20A, V_{GS}=0V,	-	23.3	-	ns
Qrr	Reverse Recovery Charge	dI/dt=100A/μs	-	16	-	nC

Notes:

1.Pulse width limited by safe operating area.

2.Pulse width ≤300us , duty cycle ≤2%.

3.V_{DD}=25V , L=100uH , R_G=25Ω , I_{AS}=24A.

www.DataSheet4U.com

www.DataSheet4U.com




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance vs. Gate Voltage




Fig 4. Normalized On-Resistance vs. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage vs. Junction Temperature

www.DataSheet4U.com

www.DataSheet4U.com




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Circuit




Fig 12. Gate Charge Circuit

www.DataSheet4U.com

www.DataSheet4U.com

Information furnished by Silicon Standard Corporation is believed to be accurate and reliable. However, Silicon Standard Corporation makes no guarantee or warranty, express or implied, as to the reliability, accuracy, timeliness or completeness of such information and assumes no responsibility for its use, or for infringement of any patent or other intellectual property rights of third parties that may result from its use. Silicon Standard reserves the right to make changes as it deems necessary to any products described herein for any reason, including without limitation enhancement in reliability, functionality or design. No license is granted, whether expressly or by implication, in relation to the use of any products described herein or to the use of any information provided herein, under any patent or other intellectual property rights of Silicon Standard Corporation or any third parties.

www.DataSheet4U.com